



Shown with
Optional Casters

PROW-8 Tabletop AutoMist Proofer

STANDARD FEATURES:

- Stainless steel construction
- Set of 4" adjustable legs
- Full view tempered glass door
- Silicone rubber gasket on doors
- AutoMist humidity system

OPTIONS:

- Warmer
- Set of four Casters

CONSTRUCTION:

- Welded stainless steel utilizing 16 and 18 gauge
- Minimum of 2" insulation
- Control panel accessible through front of unit
- Heating elements accessible inside of cabinet and through top

CONTROLS:

- Solid state controls
- Indicator light for thermostat
- Separate heat and humidity controls

DOOR SWING: • Proofer: 23-7/8"

CLEARANCE:

- Allow four inches on each side and back of unit.

SERVICE CONNECTIONS:

- Unit is shipped from factory to be hard wired on site. Single phase unit uses four wire system.
- 120/208 or 120/240 Volt single phase is standard. Please specify at time of order.
- Two 900 Watt heating elements are mounted in the sidewalls.
- A 1/4" water line is required. A water softening system should be used to minimize mineral build-up.

SHIPPING WEIGHT:

- 200 Pounds, FOB Menominee, MI 49858

DIMENSIONS:

	Height	Width	Depth
Exterior	39-3/4"	24-1/4"	31-1/8"
Interior	27-7/8"	18-3/8"	29"

CAPACITY:

	18"x26" Sheet Pans	13"x18" Sheet Pans	Spacing
Oven	8	16	3-5/16"

ELECTRICAL:

Amp Draw	120/208/1	120/208/3	120/240/1	120/240/3
L1	10	n/a	8	n/a
L2	0	n/a	0	n/a

