



UB-6/6G Oven/Proofer

STANDARD FEATURES:

- V-Air® technology
- Stainless steel construction
- Indicator lights for thermostats
- Mechanical magnetic door latches
- Door activated microswitch for fan
- Four speed fan
- Casters
- Tempered glass doors
- Separate heat and humidity controls for proofer
- Natural or LP Gas

OPTIONS:

- Internal Steam
- AutoMist Humidity
- Cook'n Hold
- Warmer in Proofer
- Solid Door (per door)
- Meat Probe

CONSTRUCTION:

- Welded stainless steel utilizing 16 and 18 gauge
- Minimum of 3" insulation
- Control panel accessible through front and side of unit
- Heating elements accessible inside of cabinet and through side of proofer

CONTROLS:

- Solid state controls
- Indicator lights for thermostats
- Burner ignition light
- Microswitch fan motor cut-off

DOOR SWING: • Oven: 25" • Proofer: 25"

CLEARANCE: • Allow four inches on each side and back of unit.

SERVICE CONNECTIONS:

- Unit is shipped from factory to be hard wired on site. Single phase uses four wire system.
- 120/208 or 120/240 Volt single phase is standard. Please specify at time of order.
- The proofer contains two 600 Watt elements and one 625 Watt element controls the manual fill humidity system.
- LP or Natural Gas – 65,000 BTU's
- A 1/4" waterline is required if a steam or AutoMist option is selected. A water softening system should be used to minimize mineral build-up.

SHIPPING WEIGHT: • 800 Pounds, FOB Menominee, MI 49858

DIMENSIONS:

| | Height | Width | Depth |
|-----------------|---------|---------|-------|
| Exterior | 83-3/8" | 32-1/4" | 36" |
| Interior | | | |
| Oven | 26-1/4" | 18-1/4" | 28" |
| Proofer | 23-3/4" | 18-1/2" | 27" |

CAPACITY:

| | 18"x26" Sheet Pans | 13"x18" Sheet Pans | Spacing |
|----------------|-----------------------|-----------------------|---------|
| Oven | 6 | 12 | 4" |
| Proofer | 6 | 12 | 3-1/2" |

ELECTRICAL:

| Amp Draw | 120/208/1 | 120/208/3 | 120/240/1 | 120/240/3 |
|-----------|-----------|-----------|-----------|-----------|
| L1 | 9 | n/a | 9 | n/a |
| L2 | 17 | n/a | 17 | n/a |

